

Safety Data Sheet

Specialty Sealant

Date: 08/30/18

Version: 2

1. Identification

1.1. Product identifier

Product Identity Specialty Sealant
Alternate Names Specialty Sealant

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use Sealant for anodized aluminum.
Application Method See Technical Data Sheet

1.3. Details of the supplier of the safety data sheet

Company Name U.S. Specialty Color Corporation
5624 Cannon Drive
Monroe, NC 28110

Emergency

24 hour Emergency Telephone No. 1-800-424-9300
Customer Service: U.S. Specialty Color Corporation 704-292-1476

2. Hazard(s) identification

2.1. Classification of the substance or mixture

Acute Tox. 4;H302	Harmful if swallowed.
Skin Irrit. 2;H315	Causes skin irritation.
Skin Sens. 1;H317	May cause an allergic skin reaction.
Eye Dam. 1;H318	Causes serious eye damage.
Resp. Sens. 1;H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Carc. 1A;H350i	May cause cancer by inhalation.
Aquatic Chronic 2;H411	Toxic to aquatic life with long lasting effects.

2.2. Label elements

Using the Toxicity Data listed in section 11 and 12 the product is labeled as follows.



Safety Data Sheet

Specialty Sealant

Date: 08/30/18

Version: 2

Danger

H302 Harmful if swallowed.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H350 May cause cancer.

H411 Toxic to aquatic life with long lasting effects.

[Prevention]:

P202 Do not handle until all safety precautions have been read and understood.

P261 Avoid breathing dust / fume / gas / mist / vapors / spray.

P264 Wash thoroughly after handling.

P280 Wear protective gloves / eye protection / face protection.

P285 In case of inadequate ventilation wear respiratory protection.

[Response]:

P301+312 IF SWALLOWED: Call a POISON CENTER or doctor / physician if you feel unwell.

P302+352 IF ON SKIN: Wash with plenty of soap and water.

P304+341+313 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice / attention.

P305+351+338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.

P333+313 If skin irritation or a rash occurs: Get medical advice / attention.

P342+311 If experiencing respiratory symptoms: Call a POISON CENTER or doctor / physician.

P363 Wash contaminated clothing before reuse.

[Storage]:

P405 Store locked up.

[Disposal]:

P501 Dispose of contents / container in accordance with local / national regulations.

3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Nickel acetate tetrahydrate CAS Number: 6018-89-9	50 - 75	Acute Tox. 4:H302 Skin Sens. 1;H317 Eye Dam. 1;H318	[1]

Safety Data Sheet

Specialty Sealant

Date: 08/30/18

Version: 2

		Resp. Sens. 1;H334 Carc. 1A;H350i Aquatic Chronic 2;H411	
Surfactant CAS Number: Proprietary	25 - 50	Skin Irrit. 2;H315	[1]
Benzoic acid CAS Number: 65-85-0	1.0 - 25	Skin Irrit. 2;H315 Eye Dam. 1;H318	[1][2]

In accordance with paragraph (i) of §1910.1200, the specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

*The full texts of the phrases are shown in Section 16.

4. First aid measures

4.1. Description of first aid measures

General	In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
Inhalation	Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious place in the recovery position and obtain immediate medical attention. Give nothing by mouth.
Eyes	Immediately flush the eyes with large amounts of water for at least 15 minutes, alternately lifting the upper and lower eyelids. After 5 minutes, if appropriate, remove contact lenses and continue flushing the eyes for an additional 15 minutes. Call a physician at once.
Skin	Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.
Ingestion	Do not induce vomiting and get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Overview	Emergency overview Warning: Contains material which may cause cancer. Harmful if inhaled. May cause allergic respiratory and skin reaction. Contact with eyes may cause severe irritation and may cause burns, loss of vision. May be harmful if swallowed. May cause sensitization by inhalation and skin contact.
Inhalation	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin	May cause an allergic skin reaction.

5. Fire-fighting measures

Safety Data Sheet

Specialty Sealant

Date: 08/30/18

Version: 2

5.1. Extinguishing media

Recommended extinguishing media; CO₂, powder, water

5.2. Special hazards arising from the substance or mixture

Hazardous composition products: Burning may produce oxides of carbon, nitrogen and sulfur.

Avoid breathing dust / fume / gas / mist / vapors / spray.

5.3. Advice for fire-fighters

Unusual fire/explosion hazards: Emits toxic fumes under fire conditions.

Fire-fighters should wear appropriate equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

ERG Guide No. ----

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8).

6.2. Environmental precautions

Do not allow spills to enter drains or waterways.

6.3. Methods and material for containment and cleaning up

Wear prescribed protective equipment. Vacuum or sweep up material and place in a designated container immediately. Prevent run off to drains, sewers or other public waterways.

Waste material may be disposed of by a licensed waste facility contractor.

7. Handling and storage

7.1. Precautions for safe handling

Avoid contact with eyes, skin, and clothing. Eating, drinking, and smoking should be prohibited in areas where this material is handled. Wash hands and face before eating, drinking, and smoking. Put on appropriate personal protective equipment (see section 8).

See section 2 for further details. - [Prevention]:

7.2. Conditions for safe storage, including any incompatibilities

Handle containers carefully to prevent damage and spillage.

Incompatible materials: No data available.

Store in original container, in a cool, dry location. Close package tightly after removal of product. Avoid dust formation.

See section 2 for further details. - [Storage]:

Safety Data Sheet

Specialty Sealant

Date: 08/30/18

Version: 2

7.3. Specific end use(s)

No data available.

8. Exposure controls and personal protection

8.1. Control parameters

Exposure

CAS No.	Ingredient	Source	Value
65-85-0	Benzoic acid	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
6018-89-9	Nickel acetate tetrahydrate	OSHA	TWA 1 mg/m3
		ACGIH	No Established Limit
		NIOSH	TWA 0.015 mg/m3
		Supplier	No Established Limit
Proprietary	Surfactant	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit

The exposure limits for nuisance dust are: OSHA PEL: 15 mg/m3 (50 mppcf*) TWA, ACGIH 10 mg/m3.

Carcinogen Data

CAS No.	Ingredient	Source	Value
65-85-0	Benzoic acid	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
6018-89-9	Nickel acetate tetrahydrate	OSHA	Select Carcinogen: No
		NTP	Known to be human carcinogen
		IARC	Group 1: Carcinogenic to humans.
Proprietary	Surfactant	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;

8.2. Exposure controls

Respiratory

If risk assessment indicates this is necessary, an appropriate NIOSH approved respirator for dust should be worn. Use type N95 (US) or type P3 (EN 140-143,149) dust masks.

Eyes

Wear safety glasses with side shields.

Skin

Wear a rubber or plastic apron. Wear clothing suitable to avoid skin contact and clean after every shift. Wear impermeable rubber or plastic gloves.

Safety Data Sheet

Specialty Sealant

Date: 08/30/18

Version: 2

Engineering Controls Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn.

Other Work Practices Eye wash fountain and emergency showers are recommended. Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details. - [Prevention]:

9. Physical and chemical properties

Appearance	Green Powder
Odor	Acetic acid
Odor threshold	Not Measured
pH	Not Measured
Melting point / freezing point	Not Measured
Initial boiling point and boiling range	Not Measured
Flash Point	Not Measured
Evaporation rate (Ether = 1)	Not Measured
Flammability (solid, gas)	Not Applicable
Upper/lower flammability or explosive limits	Lower Explosive Limit: Not Measured Upper Explosive Limit: Not Measured
Vapor pressure (Pa)	Not Measured
Vapor Density	Not Measured
Specific Gravity	Not Measured
Solubility in Water	Not Measured
Partition coefficient n-octanol/water (Log Kow)	Not Measured
Auto-ignition temperature	Not Measured
Decomposition temperature	Not Measured
Viscosity (cSt)	Not Measured
Solubility in Water	Not Measured

9.2. Other information

No other relevant information.

10. Stability and reactivity

10.1. Reactivity

Safety Data Sheet Specialty Sealant

Date: 08/30/18

Version: 2

Hazardous Polymerization will not occur.

10.2. Chemical stability

Stable under normal circumstances.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

No data available.

10.5. Incompatible materials

No data available.

10.6. Hazardous decomposition products

When used and handled as directed, none.

11. Toxicological information

Acute toxicity

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
Nickel acetate tetrahydrate - (6018-89-9)	350, Rat	No data available	No data available	2.48, Rat	No data available
Surfactant - (Proprietary)	No data available	No data available	No data available	No data available	No data available
Benzoic acid - (65-85-0)	1,700.00, Rat - Category: 4	5,000.00, Rabbit - Category: 5	No data available	17.20, Rat Category: NA	No data available

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Classification	Category	Hazard Description
Acute toxicity (oral)	4	Not Applicable
Acute toxicity (inhalation)	4	Not Applicable
Skin corrosion/irritation	2	Not Applicable
Serious eye damage/irritation	1	Not Applicable
Respiratory sensitization	1	May cause allergy or asthma symptoms of breathing difficulties if inhaled.

Safety Data Sheet

Specialty Sealant

Date: 08/30/18

Version: 2

Skin sensitization	1	May cause an allergic skin reaction.
Carcinogenicity	1A	Not Applicable

12. Ecological information

12.1. Toxicity

The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and GHS and is not classified as dangerous for the environment, but contains substance(s) dangerous for the environment. See section 3 for details

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Nickel acetate tetrahydrate - (6018-89-9)	Not Available	Not Available	Not Available
Surfactant - (Proprietary)	Not Available	Not Available	Not Available
Benzoic acid - (65-85-0)	44.60, Fish (Piscis)	100.00, Daphnia magna	9.00 (72 hr), Anabaenia inaequalis

12.2. Persistence and degradability

There is no data available on the preparation itself.

12.3. Bioaccumulative potential

Not Measured

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

12.6. Other adverse effects

No data available.

13. Disposal considerations

13.1. Waste treatment methods

Observe all federal, state and local regulations when disposing of this substance.

14. Transport information

Safety Data Sheet

Specialty Sealant

Date: 08/30/18

Version: 2

	DOT (Domestic Surface Transportation)	IMO / IMDG (Ocean Transportation)	ICAO/IATA
14.1. UN number	Not Applicable	Not Regulated	Not Regulated
14.2. UN proper shipping name	Not Regulated	Not Regulated	Not Regulated
14.3. Transport hazard class(es)	DOT Hazard Class: Not Applicable	IMDG: Not Applicable Sub Class: Not Applicable	Air Class: Not Applicable
14.4. Packing group	Not Applicable	Not Applicable	Not Applicable
14.5. Environmental hazards			
IMDG	Marine Pollutant: Yes (Nickel acetate tetrahydrate)		
14.6. Special precautions for user			
	No further information		

15. Regulatory information

Regulatory Overview	The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented.
Toxic Substance Control Act (TSCA)	All components of this material are either listed or exempt from listing on the TSCA Inventory.
WHMIS Classification	D2AE

US EPA Tier II Hazards

Fire: No
Sudden Release of Pressure: No
Reactive: No
Immediate (Acute): Yes
Delayed (Chronic): Yes

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations. Part 372:

Chemical Name: Nickel(II) acetate

CAS No: 6018-89-9

SARA-313 - Threshold Values %: 0.1

Safety Data Sheet

Specialty Sealant

Date: 08/30/18

Version: 2

SARA 311/312 Hazard Categories

Carcinogenicity

Clean Water Act

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21)

Chemical Name: Nickel(II) Acetate

CWA -Toxic Pollutant: Yes

CERCLA

To the best of our knowledge, this product does not contain chemicals at levels which require reporting under this regulation, Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

California Proposition 65

WARNING! This product contains a chemical, which is known to the State of California to cause cancer.

Chemical Name: Nickel(II) acetate

CAS No: 6018-89-9

New Jersey RTK Substances (>1%):

Benzoic acid

Nickel(II) acetate

Pennsylvania RTK Substances (>1%):

Benzoic acid

16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H302 Harmful if swallowed

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

Safety Data Sheet

Specialty Sealant

Date: 08/30/18

Version: 2

H318 Causes serious eye damage.

H334 May cause allergic or asthmatic symptoms or breathing difficulties if inhaled.

H350i May cause cancer by inhalation.

H411 Toxic to aquatic life with long lasting effects.

Issue Date: 03/25/2015

Revision Date: 08/30/2018

Revision Note: California Proposition 65

We believe all the data and information given is accurate as of the date of preparation and is offered in good faith, but without warranty or representation. Since conditions of use are beyond our control, we disclaim all liability for reliance thereon. This is offered solely for your consideration, investigation and verification.

End of Document