



# Specialty Defoamer

Defoamer

## 1. Description

Specialty Defoamer is used to control foam formation in caustic etch baths, organic dyebaths, and mid-temperature nickel acetate sealing solutions when foam generation is considered a problem.

- ☑ Non-silicone formulation.
- ☑ Low dosage provides a cost-effective treatment.
- ☑ RoHS compliant
- ☑ REACH compliant

## 2. Application instructions

**Seals:** 100 ml for every 1,000 gallons of working sealant solution.

**Etch:** 100 ml for every 1,000 gallons of working etch solution.

**Dyes:** 75 ml for every 100 gallons of working dye bath solution.

Dilute the Defoamer concentrate 1:10 before adding it to the working solution.

For spot control, spray diluted defoamer directly onto localized foam.

## 3. Titration procedure

Due to the extremely low concentration of use, there is no analytical procedure for its control. Therefore, bath control depends on the amount of foam generated and the desired level of control.

## 4. Storage

Stored in original container in an area above 32°F to prevent freezing.

## 5. Packaging

5 gallons

## 6. Product safety

We recommend that the company/operator read and review the **Safety Data Sheet** for the appropriate health and safety warnings before use.

U.S. Specialty Color Corporation® recommendations, notices or instructions as to handling, use, storage of any product, including its use alone or in combination with other products, or as to any apparatus or process for the use of any product, are based upon information believed to be reliable, but U.S. Specialty Color Corporation® shall have no liability with respect to any recommendations or instructions. U.S. Specialty Color Corporation® sole and exclusive warranty is that its products comply with U.S. Specialty Color Corporation® published chemical and physical specifications. U.S. Specialty Color Corporation® makes no other warranties, other express or implied with respect to its recommendations, instructions, products, apparatus, and process or otherwise and specifically disclaims any implied warranties of merchantability, suitability, fitness for a particular or otherwise.

Original Issue Date: 03/27/2026  
Specialty Defoamer