



Specialty Defoamer D

Anti-foam

1. Description

Specialty Defoamer D can be used to break foam bubbles and control foaming of organic dyestuffs.

- Non-silicone formulation.
- Non-flammable.
- Immediate defoaming action.

2. Application instructions

Specialty Defoamer D is added directly to dyebath if foaming is considered a problem.

Concentration: 0.02-0.04% by vol

Initial addition: For each 100 gallons of working dyebath, add 75-ml or 2.5 fluid ounces of Defoamer.

For spot control: Spray Defoamer directly on localized foam.

3. Titration procedure

There is no analytical procedure for determining Defoamer D concentration level.

Defoamer D is not consumed, replenishment is necessary as a consequence of drag-out.

Replenish in very small increments as needed to control foam.

4. Storage

Stored in original container in area above 32°F to prevent freezing.

5. Packaging

5 gallons

6. Product safety

We recommend that the company/operator read and review the **Material Safety Data Sheet** for the appropriate health and safety warnings before use.

U.S. Specialty Color Corporation® recommendations, notices or instructions as to handling, use, storage of any product, including its use alone or in combination with other products, or as to any apparatus or process for the use of any product, are based upon information believed to be reliable, but U.S. Specialty Color Corporation® shall have no liability with respect to any recommendations or instructions. U.S. Specialty Color Corporation® sole and exclusive warranty is that its products comply with U.S. Specialty Color Corporation® published chemical and physical specifications. U.S. Specialty Color Corporation® makes no other warranties, other express or implied with respect to its recommendations, instructions, products, apparatus, and process or otherwise and specifically disclaims any implied warranties of merchantability, suitability, fitness for a particular or otherwise.

4/12/12
Specialty Defoamer D