



Specialty Ni Additive

Smut Prevention Additive

1. Description

Specialty Ni Additive is specifically formulated to restore the smut preventative properties of mid temperature (160-190°F) nickel acetate sealant solutions.

Note: Do not use this additive with magnesium, low-temperature nickel-fluoride, or high temperature nickel acetate solutions.

2. Application instructions

Concentration: 0.12-0.25% by vol

Initial addition: For each 100 gallons of sealant solution, add 16 fluid ounces.

3. Titration procedure

There is no analytical analysis for Ni Additive concentration control.

At the first sign of seal smut, and still passing seal tests, add 0.12% of Ni Additive to your sealant.

4. Storage

Stored in original container in area above 32°F to prevent freezing.

5. Packaging

5 gallons

6. Product safety

We recommend that the company/operator read and review the **Material Safety Data Sheet** for the appropriate health and safety warnings before use.

U.S. Specialty Color Corporation® recommendations, notices or instructions as to handling, use, storage of any product, including its use alone or in combination with other products, or as to any apparatus or process for the use of any product, are based upon information believed to be reliable, but U.S. Specialty Color Corporation® shall have no liability with respect to any recommendations or instructions. U.S. Specialty Color Corporation® sole and exclusive warranty is that its products comply with U.S. Specialty Color Corporation® published chemical and physical specifications. U.S. Specialty Color Corporation® makes no other warranties, other express or implied with respect to its recommendations, instructions, products, apparatus, and process or otherwise and specifically disclaims any implied warranties of merchantability, suitability, fitness for a particular or otherwise.

11/1/11
Specialty Ni Additive